




## TECHNICAL DATA SHEET

# NOMATEC® BACKER ROD HOLLOW & FULL



NOMATEC® Backer Rod Hollow & Full round profiles are manufactured from closed-cell polyethylene foam and are used as backing material for elastomeric and other cold-applied sealants. They are inserted into a joint to control the sealant depth and act as bond-breakers, without adhering to the sealant.

### PRODUCT ADVANTAGES

- › Avoids the 3-way bonding
- › Specially manufactured for cold applied sealants
- › Ensures the correct elliptical shape of the flexible joint
- › Rot-proof, compressive and elastic

### PRODUCT FEATURES

- › Closed cell PE foam
- › Density 22 kg/m<sup>3</sup> ± 5 kg/m<sup>3</sup>
- › Water absorption <1 vol.% according to DIN 52459
- › Fire class: Euroclasse E (EN 13501-1)
- › Packaging: coils, without spool, in cardboard boxes or lengths in cardboard boxes
- › Colour: grey

### APPLICATIONS


- › Convenient as gap, window and door sealing
- › Extremely flexible
- › Ideal as joint insulation
- › Internal and external applications






## TECHNICAL DATA SHEET

# NOMATEC® BACKER ROD HOLLOW & FULL



Type	A	B	Density	Length	Packaging unit	Item code	 mm
	mm	mm	kg/m <sup>3</sup>	m	m/ctn		
*F 6 mm	6 +1/0	-	22 +5/-5	1500 ±2%	1500	3000145 (CPPBCF00605)	700 * 400 * 400
F 8 mm	8 +1/0	-	22 +5/-5	900 ±2%	900	3000149 (CPPBCF00804)	700 * 400 * 400
F 10 mm	10 +1/0	-	22 +5/-5	600 ±2%	600	3000151 (CPPBCF01001)	700 * 400 * 400
F 10 mm	10 +1/0	-	22 +5/-5	50 ±2%	50	3000171 (CPPBNF01000)	390 * 390 * 80
F 13 mm	13 +1/0	-	22 +5/-5	400 ±2%	400	3000152 (CPPBCF01300)	700 * 400 * 400
F 15 mm	15 +1/-1	-	22 +5/-5	250 ±2%	250	3000153 (CPPBCF01500)	700 * 400 * 400
F 20 mm	20 +1/-1	-	22 +5/-5	150 ±2%	150	3000155 (CPPBCF02000)	700 * 400 * 400
F 25 mm	25 +1/-1	-	22 +5/-5	100 ±2%	100	3000156 (CPPBCF02500)	700 * 400 * 400
F 32 mm	30 +1/-1	-	22 +5/-5	2 ±30mm	180	3000157 (CPPBCF03000)	2040 * 400 * 300
F 40 mm	40 +1/-1	-	22 +5/-5	2 ±30mm	120	3000159 (CPPBCF04000)	2040 * 400 * 300
F 50 mm	50 +1/-1	-	22 +5/-5	2 ±30mm	84	3000160 (CPPBCF05000)	2040 * 400 * 300
F 60 mm	60 +1/-1	-	22 +5/-5	2 ±30mm	126	3000161 (CPPBCF06000)	2040 * 400 * 300
**H 15-16 mm	16 +1/-1	5 +2/-2	22 +5/-5	250 ±2%	250	3000163 (CPPBCH01600)	700 * 400 * 400
H 20 mm	20 +1/-1	6 +2/-2	22 +5/-5	150 ±2%	150	3000165 (CPPBCH02001)	700 * 400 * 400
H 24-25 mm	24 +1/-1	8 +2/-2	22 +5/-5	100 ±2%	100	3000166 (CPPBCH02400)	700 * 400 * 400
H 30 mm	30 +1/-1	9 +2/-2	22 +5/-5	80 ±2%	80	3000167 (CPPBCH03000)	700 * 400 * 400
H 35 mm	35 +1/-1	11 +2/-2	22 +5/-5	1 ±30mm	180	3006379 (CPPBCH03500)	590 * 390 * 1020
H 40 mm	40 +1/-1	13 +2/-2	22 +5/-5	1 ±30mm	120	3000168 (CPPBCH04000)	590 * 390 * 1020
H 40 mm	40 +1/-1	13 +2/-2	22 +5/-5	2 ±30mm	120	3000169 (CPPBCH04001)	2040 * 400 * 300
H 50 mm	50 +1/-1	16 +2/-2	22 +5/-5	1 ±30mm	90	3000170 (CPPBCH05000)	590 * 390 * 1020
H 50 mm	50 +1/-1	16 +2/-2	22 +5/-5	2 ±30mm	84	3006380 (CPPBCH05001)	2040 * 400 * 300

\*F = Full \*\*H = Hollow



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology any time and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.





## TECHNICAL DATA SHEET

# NOMATEC® BACKER ROD HOLLOW & FULL

## INSTALLATION INSTRUCTIONS

Proper size selection is important as it controls the depth of the sealant bead. The backer rod must be oversized by 25 to 30% to fit tightly into the joint and function as a bondbreaker to prevent back-side adhesion of the sealant. The backer rod should be installed with a special designed insertion tool, to avoid any kind of damage of the rod during the installation. Prior to the placing of the backer rod, clean all joints as per the sealant and the primer manufacturer's recommendations. The application of cold applied sealants shall not begin if there is any sign of moisture on the surface or in the joint. All surfaces must be clean, dry and free of all foreign matters.

## WARRANTIES

The present information, in particular suggestions for the processing and use of our products, rests on our knowledge and experience. Because of the varying materials and the fact that the working conditions lie outside of our control, we recommend in every case that customers conduct sufficient tests of their own to satisfy themselves as to the suitability of our products for the intended procedures and processing purposes. No liability may be inferred either from the present indications or from any oral advice, unless there is premeditation or gross negligence on our part. For the rest, our General Terms of Business shall apply to any liability for defects.

## COMPLEMENTARY PRODUCTS



### NOMATEC® BACKER ROD XL

NOMATEC® Backer Rod XL round profiles are manufactured from closed cell, cross-linked polyethylen foam and are specially designed to backfill joints used with hot applied sealants. They provide the correct sealant reservoir configuration, control the depth and prevent bottom side sealant adhesion.



### NOMATEC® RDS

NOMATEC® RDS are edge expansion joints, in closed cell PE foam, for cement floor and floor heating systems.



### NOMATEC® ROOF SEAL

NOMATEC® Roof Seal are self adhesive profiles with open cell PE foam specially designed to seal the roof area. Thanks to their unique cut profile, they adapt themselves to nearly every roof shape and reliably fill gaps and fugues.



NMC reserves the right to update the product line or its technical features to the state-of-the-art technology any time and without previous announcement. All given information is to the best of our knowledge. If you have any questions concerning technical details please contact the NMC information service. Any partial reproduction or reprint shall require our explicit approval.



**NMC sa**

Gert-Noël-Strasse · B-4731 Eynatten  
☎ +32 87 85 85 00 · 📠 +32 87 85 85 11  
info@nmc.eu

**NMC Polska**

ul. Pyskowicka 15 · PL - 41807 Zabrze  
☎ +48 32 373 24 40 · 📠 +48 32 373 24 43  
E-Mail: biuro@nmc.pl



[www.nmc-nomafoam.com](http://www.nmc-nomafoam.com)